

brix glasso 930

POLYMER BASED TILE ADHESIVE FOR FIXING GLASS TILES

SPECIFICATION

BS 5980:1980

DESCRIPTION

Brix glasso is a polymer modified cementitious material in white powder form, which only needs on site addition of water to make a paste, used for filling and fixing glass mosaic tiles. It is suitable for use on vertical as well as horizontal surfaces.

USAGE

Brix glasso is especially developed for fixing and filling glass mosaic tiles. Glass mosaic tile fixing technique requires the joint filling is done first and the fixing mortar is applied thereafter. Sometimes same material is used for fixing as well as joint filling. Hence glasso is made in brilliant white colour. Brix glasso not only helps in scientific fixing of the glass mosaic tiles but also makes the tiled area waterproof.

APPLICATION

Ensure that the surface to be tiled is clean and free from dust, dirt, grease etc. Mix glasso with clean water, in the proportion of 3.5: 1 powder to water in volume. Mix till a uniform consistency, smooth white paste is obtained. Leave the paste for ten minutes in the pan for the entrapped air if any, to escape and remix the paste. Apply the paste uniformly on to the surface to be tiled as well as on the back of the Glass mosaic tiles till the joints therein are effectively filled and press the tiles in position. Same day wash out the backup paper with wet scrubber.

ADVANTAGAES

- Single Component hence easy to use
- No wetting of surface to be tiled
- Makes the tiled area waterproof
- Specially developed for fixing glass mosaic tiles.

PROPERTIES

Bulk Density	:	1650kg/m ³
Pot Life of Paste	:	45 min at 35°
Form	:	Free flowing powder
Color	:	Brilliant White

COVERAGE

1 kg of glasso yields a 600cc of white paste. Glass mosaic tiles when fixed with uniform thin bed will cover an area of 5-6sqft/kg.

PACKING

20kg bags.

SELF LIFE

12 months if stored in manufacturer's original packing in a cool and dry place away from moisture and heat.

QUALITY ASSURANCE

brix products are manufactured under strict quality control measures as per manufacturing specifications. If the behavior of the product is varying from the claims in the data sheets stop the use of the product and contact the nearest brix representative

Note : Two component system : Glasso of 20kgs with 1ltr. Acrylic polymer for vertical cladding system.