

brix tile grout 950

POLYMER BASED TILE GROUT IN DIFFERENT COLOURS

DESCRIPTION

Brix tile grout is a polymer based cementitious tile joint filler used in filling gaps and levels itself to give hard wearing, non-dusting tile joints.

PRIMARY USE

To provide smooth water-resistant hard wearing tile joints.

TYPICAL APPLICATION

As a tile joint filler in domestic floor and wall tiles of domestic and other commercial establishments, laboratories, bakeries, super markets, showrooms, hospitals etc.

ADVANTAGES

Brix tile grout does not allow moisture/ water to seep into the back of the tile and cause its dislocation. It firmly holds the tiles together to give a long life to the floor tiles. It is available in 16 pleasing colours to match the colours of tile. (Ask for shade card). It is recommended for filling joints up to 6mm width. High compressive, tensile & flexural strengths ensure carefree joints up to the life of the tile. It is waterproof and does not peel or crack. It is Non-dusting. It is easy to use and clean.

DIRECTION FOR USE

Add 3 to 3 ½ parts **brix** tile grout to one part of water by volume. Mix to a smooth consistency. Let the paste stand for 15 minutes before using.

Apply the paste to the tile joints with a sponge/squeeze trowel. Remove surplus **brix** tile grout with a damp sponge.

Allow, 24 hours for the filling to dry. Then polish the tile with a clean, dry cloth.

NOTE

BRIX TILE GROUT must be filled within 24hrs of fixing the tiles.

COVEREAGE

Depends on the size of the tile and width of the joint, for 3 mm deep joints coverage is given in the utility chart below.

Brix tile grout utility chart

Coverage per kg of **brix** tile grout in square feet

JOINT WIDTH	6"X6"	6"X12"	8"X8"	8"X12"	10"x10"	12"x12"
2 mm	93	128	128	152	158	186
3 mm	47	64	64	76	79	93
4 mm	31	43	43	51	53	62

COLOURS

Brix tile grout is available in 16 pleasing colours.

PACKING

1kg and 20kg.

SHELF LIFE

12 months if stored in manufacturer's sealed packs in a cool and dry place away from moisture and heat.

QUALITY ASSURANCE

brix products are manufactured under strict quality control measures as per manufacturing specifications. If the behavior of the product is varying from the claims in the data sheets stop the use of the product and contact the nearest **brix** representative.